
Eddie Dow Ltd.

15 - 16 SOUTHAM ROAD, BANBURY, OXON. ENGLAND

TELEPHONE 4287 (TWO LINES)

Hours of Business: 9 a.m. — 6 p.m. Daily Workshop Closed after 1 p.m. Saturday

Custom Components and Performance Equipment for the B.S.A. Gold Star



PETROL AND OIL TANKS

Brealey-Smith moulded Plastic Petrol Tank. Nominal capacity 5 Gallons. Self coloured in White, Red, Light Blue and Black. Gold Lined 35/- extra. Brass Tap Bosses. Chrome Monza Filler Cap. Stainless steel mounting Strap with Rubber insulating band. ...

 \pounds s. d.

12 19 6

			3.	u.	
Fi-Glass Petrol Tanks in 3, 4 and 5 g combined Petrol/Oil Tanks. (Illustrated leaflet of all types	on request.)				
Lyta 5 Gallon Polished Alloy Tan and Twinfeed. Centre bolt mounti	k with Monza Cap de	live	ry o	n	
Fi-Glass Road Racing Central Oil Q.A. Cap. Replaces battery. Supp to mount on standard platform.	olied c/w all fittings	0	10	0	
Also available with Side Filler N for Scrambles use or if Cutaway S	eck and Screw Cap Seat is not fitted 1	0	10	0	
Monza Q.A. Filler Caps for Petrol		1	18	6	
Alloy Collars Threaded to take M Bonding or Welding to Tank	Ionza Filler Cap for		5	0	
RACING CLUBMAN AF	ND SCRAMBLES SEATS				
T.D. Mk. V Racing Seat. Glassf Sorbo padded cutaway for oil t direct to sub-frame necessitating r	ank filler cap. Fits				
guard. Gives lowest possible ridin	g position	5	0	0	
Tubular steel support loop for M		1	10	0	
T.D. Mk Glassfibr	c. II Clubmans Seat. re base. Fits over I rear mudguard and	5	0	0	
B.S.A. Gold Star Scrambles Seat very tough vinyl cover. Original	t. Now fitted with	6	0	0	
Manx Pattern Racing Seat. Ultra adapted to fit B.S.A. sub-frame.		4	7	6	
Brealey-Smith Dual Racing Seats (Illustrated leaflets available	s and Fi-Glass seats. e on request.)				
SILENCERS AND	EXHAUST PIPES				
E.D. Gold Star Extractor Silences Clubmans Exhaust pipe	rs to fit standard $1\frac{3}{4}$ "	2	17	6	
m. Sv	D. Gold Star Club- ans Exhaust pipe. vept back design for se with E.D. Silencer				
134	Diameter	2	17	6	

		£	s.	d.	
E.D. Gold Star Scrambles Exhaust pipe. 2 piece fitting over and behind footrest. Used by all B.S.A. Riders at home and abroad	e design		12		
E.D. 500 c.c. Gold Star Road Racing Exhaust p	oipe 1 <u>7</u> ″	2	14	6	
E.D. Scrambles Silencer—Short barrel type, esilencing without loss of performance. finished, $1\frac{3}{4}$	effective Chrome 	1	12	6	
HANDLEBARS AND STEERING C	OMPONE	1 T	S		
E.D. "Superleggera" Front Fork Conversion F Racing.	or Road				
Kit Consists of High Tensile Alloy Fork Yoke. Incor Mounting Boss for RevCounter and Speedo	porating Plate	3	15	0	
Lengthened Ph Upper Fork Bu	ıshes	2	14	0	
l Pair Fork Rods		1	5	6	
Alloy Steering Knob and Rod		1	_	0	
1 Pr. Fork Oil 1 Locknut for	Steering		7	6	
Stem adjuster. Price of Comp		9			
Detailed Fitting Instructions supplied with e		_			
This Race proved conversion for B.S.A. Forks, handling at high speed and during heavy consistent with, and essential for Road Racir is reduced to 4". Compression of fork rest improved clearance when cornering. Damper two-way hydraulic damping. Lengthened by judder under heavy braking.	is designed to y braking, o ng. Overall r	nov	vem	ent ent	
E.D. Fork Gaiters. Now made in neoprene resistant to oil and grease. Small convolution good flexibility and long life	ns. Give		15	0	
Set of 4 Gaiter clips			6	0	

E.D. Headlamp Bracket Kit. Heavily Chromed. "U" Bracket has adjustable clips to facilitate mounting to most types of Tele Fork. Kit Complete 1 12 6



Lucas 7" all Chrome Headlamp assembled with Q.A. Plug for harness. Ammeter and switch	7	10	0
Clip-on Handlebars Per pair	2	2	0
Amal all Alloy Clutch and Brake Levers with built in Adjusters	1	6	9
Vincent and Ace Type Handlebars From		12	6
E.D. Scrambles Handlebars. Braced and Lined. Chrome plated	1	15	0
Amal Chrome Q.A. Twistgrip assembly		14	6
Alloy Q.A. Twistgrip assembly	1	12	6
All Nylon Q.A. Twistgrip assembly		19	6
"Supergrip" Vaned Grips Per pair		2	6

DUNLOP RACING TYRES

	£	S.	d.	
Triangular — 350 x 19 Rear Cover	7	17	6	
Triangular or Ribbed front Cover 300 x 19	7	8	6	
Full Range of Dunlop and Avon Tyres Stocked, including Trials and Scrambles Tyres.				
Security Bolts for Alloy Rims. WM1 and WM2		13	6	

W. & S. VALVE SPRINGS

A Must for engines tuned and capable of exceeding standard R.P.M. range. No breakages ever reported



TECHNICAL DETAILS


Optimum installed length $l \frac{5}{16}$ seat poundage at $l \frac{5}{16}$ 80 lbs. Full lift poundage (.440 lift) 230 lbs. Silicon-Chrome wire ground to final dimension. Shot peened after forming 20% greater tensile strength than carbon steel spring wire for DB 350, DB, and DBD 500 engines Per set	4	15	0	
DDD 300 engines rei see	-	13	·	
HIGH COMPRESSION PISTONS				
500 c.c. 9 - 1 CR. STD. +020 +040. B.S.A. Full Skirt type	3	7	0	
500 c.c. 10 - 1 CR. STD. +020 +040. Semi Slipper type only	5	0	0	
350 c.c. 9 - 1 CR. STD. $+020$. Hepolite Manufacture.	6	4	6	
E.D. INDUCTION SPACER BLOCKS				
Polished Alloy. 1" Thick 65 mm. Stud centres. $l_{\bar{1}\bar{6}}$ " choke for 350 c.c. $l_{\bar{2}}$ " for 500 c.c. Supplied c/w Lengthened studs	1	0	0	
E.D. Alloy Tappet Covers. Polished Finish. Enhances appearance. Cuts out oil leaks.				
Supplied c/w Allen Screws and		12	6	

		and Rocker S leaks, reduc fractures. Oi	ocker Oil-Feed Spindle Bolts. es possibility I feed pipe, wa	Cures of p	oil oipe	£	S.	d.	
		supplied.		•••	•••		17	6	183
	Alloy Blank Plu	g to replace \	Valve Lifter.	•••			1	9	
	Engine Sprocke	ts 16 to 24 T	eeth				16	6	
	Air Intake Velo effect increases efficiency thro	Monobloc C carb. Double Increased vo frothing, previews feeds neat fur float to control to the c	ow revs. Impr opening s	sizes r capac , redu starvat atly ass evel— Desig . Supp ial gasi bloc. F oves ca	of city. uces ion. sists The ned lied ket.		16	6	
	Immediate impr	ovement to a	cceleration.	•••	•••		9	0	
		CYC	CLE PARTS						
			Fi-Glass Prim Guard. Full to comply w F.I.M. Ruling.	Loop t	уре	3	15	0	
	E.D. Primary Cengine plates. C				on	2	10	0	
D. D.	E.D. Chain Oile Type screw top pipe. Suitable 1	c/w mounting	g bracket. Tap	and f		1	15	0	
	F		- condairy C						

Alloy Mudguards

4" × 19"	Rear	 	 	1	0	0
3" × 19"	Front	 	 		15	0
3" x 21"	Front	 	 1		15	0

£ s. d.



Norwell Alloy Brake Muff. Precision machined from $\frac{1}{2}$ " Dural 15" diameter. Periphery tapered to $\frac{1}{8}$ ". Shrunk on to B.S.A. 8" hub after removal of outer fins. Prevents flexing and distortion of hub. Dissipates heat rapidly, minimising brake fade. Can be fitted to new machine or to own wheel. Delivery 10-14 days. Price including fitting. ... £8 10 0

	£	s.	d.
E.D. Front Brake Air Scoop for 8" brake. Polished			
Alloy. C/w Gauze and fixing screws		15	0
Jig fitted to owner's back plate	1	10	0

MISCELLANEOUS ITEMS

DBD 500 c.c. Owners Handbook	4	6
B.S.A. Gold Star 3" Diameter Pocket Badge	6	0
B.S.A. Gold Star Lapel Badge	2	0
B.S.A. Ties—Gold Star on Maroon or Blue Background	14	6
Alloy Blank Plug for Outer Gearbox Cover to replace k/start spindle	2	6
Blanking Nut for speedo drive union on gearbox casing	2	6

B.S.A. GENUINE SPARES

A full range of B.S.A. Spares is stocked for all models including Gold Star. Although the Gold Star is now out of production, the factory maintain a good supply of essential spares. When items are no longer obtainable we manufacture proprietary patterns. As this catalogue shows we have built up the largest possible stock of spares and will always purchase new unused spares returned to us in undamaged condition to meet future demand from Gold Star owners all over the world.

GOLD STARLETS

This series of hints and tips compiled by Eddie Dow is now available in printed form and will be sent on receipt of a 10d. stamp.