

# HINTS AND TIPS ON —SERVICE—

For **BSA** and **ARIEL** Dealers

Service Bulletin #101

April 3, 1961

## NEW RUBBER MOUNTED VOLTAGE REGULATOR

A new style Voltage Regulator with rubber isolation mount, is fitted to machines on and after the following frame numbers:

A7 & A7SS	#GA7-8124
A10	#GA7-8324
A10 S.R.	#GA7-8319
Gold Star	#CB32-9848

In the event of failure of an earlier type Voltage Regulator, we recommend that it be replaced by the latest rubber mount type of regulator, part #37221.

### Installation Instructions:

1. Attach two mounting brackets to the Voltage Regulator with the "feet" of the bracket turned inwards.
2. Place the Voltage Regulator with mounting brackets inside the tool box so that there is clearance all around the unit and scribe the drilling points through the bracket holes.
3. Drill 2 9/32" holes through the tool box.
4. Attach the wires to the Voltage Regulator and assemble it in position with 1/4" bolts.

Parts required may be ordered from our parts department according to the part numbers listed below:

1	37221	Voltage Regulator	16.75
2	42-9264	Mounting Brackets	.36 each
2	2-204	Mounting Bracket Bolts	.11 each
2	2-2395	Mounting Bracket Nuts	.09 each
2	27-8560	Washers (Plain)	.04 each
2	29-541	Washers (Lock)	.03 each

Yours very truly,  
BSA Incorporated

*Walter Brown*

Walter Brown  
Service Manager

WB:ah

**BSA** Incorporated, 639 Passaic Avenue, Nutley N. J.