

HINTS AND TIPS ON — SERVICE —

For **BSA** and **ARIEL** Dealers

Service Bulletin #170

August 28, 1964

SPEEDOMETER AND TACHOMETER ON THE A65-2L A65-2SPH - A65-1T AND A50-2C MODELS

HOW TO REMOVE THE INSTRUMENTS FROM THE RUBBER MOUNTINGS:

1. Pull the trip re-set knob out of the speedometer.
2. Disconnect the drive cable.
3. Turn back the lip of the rubber mounting and brush a liberal amount of gasoline around and between the rubber and the instrument to make the rubber pliable and slippery.
4. Then push the instrument out of the rubber mounting with a blunt instrument inserted through the hole in the mounting bracket.

DO NOT USE A SCREWDRIVER AS IT WILL DAMAGE THE INSTRUMENT CASE.

DO NOT ATTEMPT TO REPAIR THE INSTRUMENTS AS THE SMITH DISTRIBUTOR - NISONGER CORPORATION - ADVISES THE WARRANTY IS VOID WHEN THEY HAVE BEEN OPENED.

When replacing the instruments in the rubber mounts, brush a liberal amount of gasoline around the rubber and push the instrument in place by hand.

WB/jc

Walter Brown
Walter Brown,
Service Manager