

HINTS AND TIPS ON —SERVICE—

For **BSA** *and* **ARIEL** *Dealers*

Service Bulletin #62

August 18, 1959

NEW IMPROVED C-15 TANK MOUNTING

In order to relieve pressure on the petrol tank, softer material is being used for the rubber sleeve, Part No. 42-8017, and buffers, Part No. 40-8038. The new parts are interchangeable with the old if two plain steel washers are fitted to the mounting bolt.

To fit the new parts:- (See diagram attached)

1. Disconnect the petrol pipe at the carburettor and remove the petrol tank.
2. Remove the three rubber buffers from the frame and the rubber sleeve from the tank and replace with the new parts.
3. Remove the mounting bolt from the frame lug, slide the larger steel washer, Part No. 29-5655, down the bolt shank and replace the bolt with the washer inside the lug, as show in the sectioned drawing. Slide the smaller washer, Part No. 2-923, over the bolt so that it rests on top of the lug.
4. Place the tank over the mounting bolt, push the distance tube through the rubber sleeve and over the mounting bolt and re-fit the original 5/16" washer and nut.
5. Re-connect the petrol pipe.

BSA INC. — SERVICE BULLETIN

MODEL C-15 PETROL TANK MOUNTING

PAGE # 2

AUG. 15 1959

